

T-CLASS™ TSA/TPA Air Conditioner and Heat Pump Performance Specifications

			COOLING DATA ^{2, 3}		HEATING DATA ^{4, 5}				PHYSICAL DATA		
			ARI RATED CAP. [Btuh]	EFFICIENCY [EER]	CAPACITY [Btuh]	17F COP	CAPACITY [Btuh]	47F COP	DIMENSIONS H X W X L [INCHES]	SHIP WT. [LBS.]	
AIR CONDITIONERS	NOM TON.	MODEL	SOUND RATING DB ¹								
	6	TSA072S4S	81	71,000	11.2	—	—	—	—	48.75 x 37.625 x 46.125	325
	7.5	TSA090S4S	81	92,000	11.3	—	—	—	—	48.75 x 37.625 x 46.125	375
	10	TSA120S4S	86	113,000	11.2	—	—	—	—	48.75 x 57.875 x 41.375	490
	10	TSA120S4D	85	108,000	11.7	—	—	—	—	48.75 x 57.875 x 41.375	505
	12.5	TSA150S4D	86	142,000	11.2	—	—	—	—	48.75 x 57.875 x 41.375	560
	15	TSA180S4D	88	190,000	11.6	—	—	—	—	48.75 x 57.875 x 86.5	800
	20	TSA240S4D	89	236,000	11.3	—	—	—	—	48.75 x 57.875 x 86.5	890
HEAT PUMPS	7.5	TPA090S4S	85	89,000	11.0	50,000	2.25	88,000	3.30	48.75 x 57.875 x 41.375	460
	10	TPA120S4S	86	112,000	11.0	70,000	2.25	116,000	3.30	48.75 x 57.875 x 41.375	540

¹Sound rating number in accordance with test conditions included in ARI Standard 270.

²6-ton-and-over equipment certified in accordance with ULE certification program, which is based on ARI Standard 340/360.

³Cooling ratings, 95°F (35°C) outdoor air temperature and 80°F (27°C) db/67°F (19°C) wb entering indoor coil air.

⁴High-temperature heating ratings, 47°F (8°C) db/43°F (6°C) wb outdoor air temperature and 70°F (21°C) entering indoor coil air.

⁵Low-temperature heating ratings, 17°F (-8°C) db/15°F (-9°C) wb outdoor air temperature and 70°F (21°C) entering indoor coil air.

NOTE: Due to Lennox' ongoing commitment to quality, all specifications, ratings and dimensions are subject to change.