

T-Class™ standard-efficiency AC/HP performance specifications

				COOLING DATA ^{2, 3}			HEATING DATA ⁴			PHYSICAL DATA	
	NOM TON.	MODEL	SOUND RATING dB ¹	ARI RATED CAP. [BTUH]	EFFICIENCY [SEER] ⁵	EFFICIENCY [EER]	EFFICIENCY [HSPF] ⁶	CAPACITY [BTUH]	COP	DIMENSIONS H X W X L [INCHES]	SHIP. WT. [LBS.]
AIR CONDITIONERS	3	TSA036S4	76	36,000	14.5	12.0	—	—	—	29.25 x 24.25 x 24.25	135
	3.5	TSA042S4	80	42,000	14.0	12.0	—	—	—	29.25 x 28.25 x 28.25	178
	4	TSA048S4	80	51,000	14.5	12.5	—	—	—	37.25 x 28.25 x 28.25	194
	5	TSA060S4	80	60,500	13.5	11.5	—	—	—	33.25 x 28.25 x 28.25	218
HEAT PUMPS	3	TPA036S4	76	37,000	14.2	12.0	8.7	36,000	3.96	33.25 x 24.25 x 24.25	180
	3.5	TPA042S4	80	44,500	14.0	12.0	8.7	42,000	3.76	33.25 x 28.25 x 28.25	220
	4	TPA048S4	80	49,500	13.5	12.0	8.7	46,000	3.54	37.00 x 28.25 x 28.25	250
	5	TPA060S4	80	59,500	13.5	11.2	8.0	56,500	3.36	43.25 x 28.25 x 28.25	255

T-Class high-efficiency AC/HP performance specifications

				COOLING DATA ^{2, 3}			HEATING DATA ⁴			PHYSICAL DATA	
	NOM TON.	MODEL	SOUND RATING dB ¹	ARI RATED CAP. [BTUH]	EFFICIENCY [SEER] ⁷	EFFICIENCY [EER]	EFFICIENCY [HSPF] ⁸	CAPACITY [BTUH]	COP	DIMENSIONS H X W X L [INCHES]	SHIP. WT. [LBS.]
AIR CONDITIONERS	3	TSA036H4	76	35,800	16.0	13.5	—	—	—	37.25 x 28.25 x 28.25	164
	3.5	TSA042H4	78	43,000	15.5	13.0	—	—	—	29.25 x 28.25 x 28.25	198
	4	TSA048H4	78	49,500	15.2	12.5	—	—	—	37.25 x 28.25 x 28.25	221
	5	TSA060H4	80	58,000	15.0	12.5	—	—	—	33.25 x 32.25 x 32.25	238
HEAT PUMPS	3	TPA036H4	79	36,600	15.7	13.5	9.0	35,600	3.94	31.25 x 32.25 x 32.25	212
	3.5	TPA042H4	79	44,500	15.5	13.0	9.7	45,500	4.08	39.00 x 32.25 x 32.25	257
	4	TPA048H4	80	50,500	15.2	13.0	9.2	49,000	3.90	39.00 x 32.25 x 32.25	262
	5	TPA060H4	80	60,500	15.0	12.5	9.0	58,000	3.64	45.25 x 32.25 x 32.25	307

¹Sound rating number in accordance with test conditions included in ARI Standard 270.

²5-ton-and-under equipment certified in accordance with ULE certification program, which is based on ARI Standard 210/240.

³Cooling ratings, 95°F (35°C) outdoor air temperature and 80°F (27°C) db/67°F (19°C) wb entering indoor coil air.

⁴High-temperature heating ratings, 47°F (8°C) db/43°F (6°C) wb outdoor air temperature and 70°F (21°C) entering indoor coil air.

⁵Up to 14.5 SEER when the T-Class TSA048S4 split system is matched with the CX34-62C coil and the SL280UH110XV60C furnace.

⁶Up to 8.7 HSPF when the T-Class TPA042S4 split system is matched with the CR33-50/60 and EL180DF110E60C furnace.

⁷Up to 16.0 SEER when the T-Class TSA036H4 split system is matched with the CX34-49 indoor coil and SLP98UH090XV48C furnace.

⁸Up to 9.7 HSPF when the T-Class TPA042H4 split system is matched with the CH23-68 indoor coil and EL180UH135E60D furnace.

Note: Due to Lennox' ongoing commitment to quality, all specifications, ratings and dimensions are subject to change.